

Jeffcat TD-100 catalyst CAS111-42-2 Huntsman

Jeffcat TD-100 is a tertiary amine catalyst used in the production of polyurethane foam. It is a clear, colorless liquid with a mild odor. Jeffcat TD-100 is compatible with most common polyols and isocyanate systems. It is also compatible with water-based systems.

Physical and chemical properties:

Properties	value
Looks	Clear colorless liquid
Scent	Mild
pH	10.5
Specific Gravity	1.02
Flash Point	100 degrees Fahrenheit
Spontaneous combustion	450 degrees Fahrenheit

temperature	
Solubility	Miscible with water, alcohols and ketones
Stable	Stabilize at room temperature

CAS number

111-42-2

Molecular Formula

C₁₂H₂₃N

Molecular weight

171.29 g/mole

Apply

Jeffcat TD-100 is used to catalyze the reaction of polyols and isocyanates to produce polyurethane foam. It is used in a variety of applications including:

Rigid foam

Soft foam

Spray foam

Forming foam

Styrofoam

Precautions for use

Jeffcat TD-100 is a flammable liquid and should be handled with care. It should be stored in a cool, dry place away from heat sources and open flames. Jeffcat TD-100 can irritate skin and eyes. If it comes into contact with skin or eyes, wash the affected area immediately with soap and water. If inhaled, move to fresh air and seek medical attention if breathing becomes difficult.

Consult the safety data sheet for more information about the Jeffcat TD-100.



Shelf Life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent moisture and other substances from mixing and affecting the product performance. Do not inhale dust and avoid contact between skin and mucous membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and change after work. Store contaminated clothes separately and use them after washing. Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com